



SolidFeel® EVA Underlay

Material Data Sheet

Product Description

This underlayment provides superb sound and moisture protection. This underlayment will absorb minor imperfections in the sub-floor, giving your laminate flooring and rigid core vinyl flooring a smooth, even surface to float upon.

Technical Specification

Product Name	EVA Underlayment
Code No.	EVA2.0; EVA3.0
Type	Sound + Vapor Barrier
Thickness	2.0mm; 3.0mm
Material	Ethylene Vinyl Acetate + PE/Aluminum Film
Regular Color	Black, Grey, Green & Orange
Subfloor Compatibility	All Types
Floor Compatibility	Laminate + Rigid Core Vinyl
Installation Method	Floating
Recommended Usage	Residential & Light Commercial
Density	110kgs/m ³
IIC (Impact Insulation Class)	73db
STC (Sound Transmission Class)	72db
Sound Insulation	22db
Water Absorption 28 Days	★★★★★
Water Vapor Diffusion	★★★★★
Thermal Insulation	★★★★★
Moisture Proof	★★★★★
Suitable for Under-floor Heating	★★★★★
Durability	★★★★★
Mechanical Stress Rating	★★★
Package	Packed in rolls with PE wrapped

Product Features

1. Advanced waterproof and excellent moisture protection.
2. Maximum sound reduction.
3. Easy to install.
4. High density with heavy weight construction.
5. Self sealing lip and tape system for easy installation.
6. Suitable for use over concrete and wood subfloors.
7. Safe for radiant heat flooring systems.
8. Reduces floor noise with excellent sound absorption.