



SolidFeel® EPE Underlay

Material Data Sheet

Product Description

Blue Foam Underlayment is our basic underlayment option and a great choice for all laminate installations. The foam has an attached moisture barrier film and the added feature of an adhesive strip. This Blue Foam will absorb minor imperfections in the sub-floor, giving your laminate floor a smooth, even surface to float upon.

Technical Specification

Product Name	EPE Underlayment
Code No.	EPE2.0; EPE3.0
Type	Vapor Barrier
Thickness	2.0mm; 3.0mm
Material	Polyethylene + PE/Aluminum Film
Regular Color	White & Blue
Subfloor Compatibility	All Types
Floor Compatibility	Laminate
Installation Method	Floating
Recommended Usage	Residential & Light Commercial
Density	20kgs/m ³
IIC (Impact Insulation Class)	58db
STC (Sound Transmission Class)	55db
Sound Insulation	19db
Water Absorption 28 Days	★★★★★
Water Vapor Diffusion	★★★★★
Thermal Insulation	★
Moisture Proof	★★★
Suitable for Under-floor Heating	★★★★★
Durability	★★★
Mechanical Stress Rating	★
Package	Packed in rolls with PE wrapped

Product Features

1. High thermal insulation.
2. Closed cell foam for excellent moisture protection.
3. Anti-crush technology for excellent performance and long life.
4. Mold and mildew resistance adds protection.