



RhinoCross®
Low-profile Access Flooring




CS 501/502 Triangle Panel

RhinoCross® triangle panels are manufactured from high quality galvanized steel formed in a triangle structure, is the primary tile used for low ceiling areas available from 40mm to 60mm height perfect for existing buildings that were not designed for traditional access floors, the galvanized steel modular tiles snap-in together very easily, and strictly for voice and data applications. This user-friendly series is readily installed and removed.

RHINO®
Strive for perfection!

Panel



1 All-steel Plate

A triangle design high quality galvanized steel made floor tiles interlock with supports without screws or adhesives.
Material: High quality galvanized steel
Thickness: 1.5/2.0mm

Description

RhinoCross® triangle panels are manufactured from high quality galvanized steel formed in a triangle structure, is the primary tile used for low ceiling areas available from 40mm to 60mm height perfect for existing buildings that were not designed for traditional access floors, the galvanized steel modular tiles snap-in together very easily, and strictly for voice and data applications. This user-friendly series is readily installed and removed.

Features

- Easy to assemble and remove
- Quiet, with a solid feel underfoot
- Galvanized steel for 100% rust corrosion protection
- 100% recyclable and eco-friendly

Panel Type	Panel Size	Top Steel Plate	Panel Construction	Panel Thickness (Nominal)	System Weight (Typical)
CS 501	21x21mm	11.00 mm	Galvanized steel converted triangle	1.50 mm	18.60 kg/m ²
CS 502	21x21mm	11.00 mm	Galvanized steel converted triangle	2.00 mm	23.88 kg/m ²

System



1 Supports

A column designed plastic supports equipped with grooves overhead interlock with tiles for a tight fit.
Material: Vinyl plastic
Height: 40mm to 60mm

Pedestal

1 Plastic Pedestal

H=35mm, 45mm, 55mm



Performance

- This low-profile access floor system is tested in accordance with PSA MOB PS/SPU specification.
- Panel deflection at centre edge must not exceed 2.5mm
- Performance to a safety factor of 2 x static load
- Structural performance based upon a full Rhino access floors system i.e. panels & pedestals.



Panel Type	Panel Grade	Concentrated Load		Uniformly Distribution Load	Ultimate Load
		Point Load	Load Over		
		25mm x 25mm square	300mm x 300mm square		
CS 501	Medium Duty	3.00 kN	4.50 kN	8.00 kN/m ²	6.00 kN
CS 502	Heavy Duty	4.50 kN	5.56 kN	12.00 kN/m ²	9.00 kN

RHINO[®]

Strive for perfection!

Corporate Headquarters

111 S.K.V. Building, 4th Floor
Soi Sansabai, Klongton
Klongtoey, Bangkok 10110
Thailand

T/ (662) 661 2990

F/ (662) 661 2991

China Office

593, Tongjiang Road
Jintian Plaza 828-830
Changzhou 213022
Jiangsu, China

T/ (86) 519 8988 3171

F/ (86) 519 8988 3901

Hong Kong Office

Unit 908, 9/F, LT Tower
31 Chong Yip Street
Kwun Tong, Kowloon
Hong Kong

T/ (852) 2865 6816

F/ (852) 2865 6813

Production Unit

Hengshanqiao
Wujin District
Changzhou 213119
Jiangsu, China

T/ (86) 519 8860 7959

F/ (86) 519 8860 5659

www.RhinoAccessFloors.com