



The system floor pedestal type RSP101 M18 from galvanized steel in combination with a noise deaden gasket and aluminum cross-head is used as substructure with raised access floor systems. The system floor pedestals are entirely made by Rhino, from the design to the production including galvanization.

The system floor pedestal type RSP101 M18 creates a noise deaden gasket designed to keep the panels separated by less than 0.7 mm at all time. The system floor pedestal type RSP101 M18 offers exceptional flexibility by its high loadability and the high adjustment range. The pedestals are infinitely adjustable on height and can therefore take up irregularities of the subfloor.

Features

- Excellent acoustic performance
- Easy installation
- High corrosion protection
- Zinc-whisker free

TECHNICAL DETAILS

Upper pedestal part	
Head assembly	Aluminum die-casted
Gasket	Noise Deaden Gasket
Lower pedestal part	
Foot plate	90 x 90 mm
Thickness	3.0 mm
Threaded bolt	M18

STATIC

Ultimate load centric	≥ 22 kN
-----------------------	---------

CORROSION PROTECTION

Corrosion protection class	Galvanized & blue passivated
Salt spray fog test	72 hours

PEDESTAL VARIANTS

FFH	Part number	Adjustment range
50 mm	RSP101-M18-50	50 - 80 mm
85 mm	RSP101-M18-85	70 - 100 mm
100 mm	RSP101-M18-100	85 - 115 mm
130 mm	RSP101-M18-130	115 - 145 mm
150 mm	RSP101-M18-150	135 - 165 mm
180 mm	RSP101-M18-180	165 - 195 mm
200 mm	RSP101-M18-200	185 - 215 mm

FFH (Finished Floor Height) = floor tile + pedestal

We reserve the right to change specification or design and supply products which may differ from those described and illustrated without notice and without liability. ©2010-2025 Rhino Technologies Co., Ltd. RSP101-M18-v2025