



High performing multipurpose flooring, directional design, PUR PROTEC treatment

MIPOLAM® 150 is a durable, high performing flexible homogeneous multipurpose flooring suitable for most types of heavy traffic areas. It benefits from PUR Protect surface treatment with excellent cleaning characteristics, improved resistance to scratching and scuffing.

Decòrlux

Key Features

- Excellent abrasion resistance
- Available in 2 m sheet
- Flexible flooring, easy to install & weld
- Matt finish surface: enhanced design & colour
- Homogeneous vinyl flooring suitable for medium to heavy duty traffic areas

 Color number: 22

 Sheet size: 200 cm x 20 lm


 Thickness: 1.5* / 2.0

MIPOLAM® 150 is recommended for public, institutional and commercial buildings where ease of maintenance and long life under heavy traffic are required.


Colorline



1003



1004



1005



1006



2037



2093





2091



2038



2049



2048



1007



1010



1013



1014





2092



2047



2034



2046



2095



2097



2096



2095



2094

INSTALLATION

Installation should be carried out in accordance with local standards. Subfloor should be smooth, hard, clean and dry prior to laying. Where applicable the subfloor must incorporate an effective Damp Proof Membrane. The material must be allowed to acclimatize 24 hours before installation in a room temperature of between 18-24°C. All seams must be hot welded using Gerflor matching welding rod.

MAINTENANCE

No wax is needed right after installation. Maintenance should be carried out regularly to retain the appearance and durability of the floor. The floorcovering should be maintained with regular sweeping and damp mopping using a neutral cleanser. More intense cleaning should be carried out using a fine spray cleaning pad under a floor machine, or for larger areas combined machine cleaning.

Technical Specification

DESCRIPTION				
Total thickness	ISO 24346 (EN 428)	mm	1.5*	2
Weight	ISO 23997 (EN 430)	g/m ²	2500	3300
Width / Length of sheet	ISO 24341 (EN 426)	cm / lm	200 / 20	

CLASSIFICATION				
Norm / Product specification	-	-	ISO 10581 (EN 649)	
European classification	ISO 10874 (EN 685)	class	23 - 31 / 34 - 43	
Fire rating	EN 13 501-1	class	Bfl-s1	
Static electrical propensity	EN 1815	KV	<2	
Electrical resistance	EN 1081	Ω	10 ⁹ -10 ¹⁰	
Slip resistance dry	EN 13893	-	≥0.3	
Slip resistance wet	DIN 51130	class	R9	

PERFORMANCES				
Wear resistance	EN 660.2	mm	≤7.5	
Wear group	EN 649	group	M	
Type binder content	ISO 10581	type	II	
Dimensional stability	ISO 23999 (EN 434)	%	≤ 0.4	
Residual indentation	ISO 24343-1 (EN 433)	mm	≈0.05	
Castor chair test	ISO 4918 (EN 425)		OK	
Thermal conductivity	ISO 10456 (EN 12524)	W/(m.K)	≈0.25	
Colour fastness	ISO 105 - B02	degree	≥ 6	
Chemical products resistance	ISO 26987 (EN 423)	-	OK	
Anti-bacterial and fungicidal treatment	-	-	OK	
Surface treatment	-	-	PUR Protect	
Color number	-	-	22	

ENVIRONMENT / INDOOR AIR QUALITY				
TVOC after 28 days	ISO 16000 - 6	µg/m	< 10	
Certification	-	-	Floorscore	

CE MARKING				
	EN 14041	-		

* Special order, minimum quantities needed

Decorlux

©2023/MIP150/V01

Factory

Wuxi Decorlux Floor Co., Ltd.
2 Jishan Road, Jiangyin
Wuxi 214445
China
Info@Decorlux-Group.com
www.Decorlux-Group.com

Headquarters

593 Tongjiang Road
Century Jintian 828-830
Changzhou 213022
China
Phone +86 519 8988 3171
Fax +86 519 8988 3901

Important Note:

We reserve the right to change specification or design and supply products which may differ from those described and illustrated without notice and without liability. ©2023 Wuxi Decorlux Floor Co., Ltd.
Commercial Reg. No.: 9132028MACMDTXK27
VAT Reg. No.: 9132028MACMDTXK27